

Technical specification

| Function | | Measuring range | Resolution | Accuracy |
|-----------------------|----------------------------|--|--------------------------------|---|
| CONTINUITY | Test Current 7 mA 2-wire | 0.00 Ω ... 19.99 Ω 20.0 Ω ... 1999 Ω | 0.1 Ω 1 Ω | ±(5 % of r. + 5 digits) |
| | Test Current 200 mA 2-wire | 0.00 Ω ... 19.99 Ω 20.0 Ω ... 199.9 Ω 200.0 Ω ... 1999 Ω | 0.01 Ω 0.1 Ω 1 Ω | ±(3 % of r. + 3 digits) ±(5 % of r.) ±(5 % of r.) |
| INSULATION RESISTANCE | Test Voltage 50/100/250 V | 0.00 MΩ ... 19.99 MΩ 20.0 MΩ ... 99.9 MΩ 100.0 MΩ ... 199.9 MΩ | 0.01 MΩ 0.1 MΩ | ±(5 % of r. + 3 digits) ±(10 % of r.) ±(20 % of r.) |
| | Test Voltage 500/1000 V | 0.00 MΩ ... 19.99 MΩ 20.0 MΩ ... 199.9 MΩ 200 MΩ ... 999 MΩ | 0.01 MΩ 0.1 MΩ 1 MΩ | ±(5 % of r. + 3 digits) ±(5 % of r.) ±(10 % of r.) |
| RCD | RCD Uc | 0.00 V ... 19.99 V 20.0 V ... 99.9 V | 0.1 V | (-0%/±15 %) of r. ± 10 digits (-0%/±15 %) of r. |
| | RCD (t), | 0.0 ms ... 40.0 ms 0.0 ms ... max.time | 0.1 ms | ±1 ms ±3 ms |
| | RCD I Ramp | 0.2xI _{ΔN} ... 1.1xI _{ΔN} (AC) 0.2xI _{ΔN} ... 1.5xI _{ΔN} (A), I _{ΔN} ≥30 mA) 0.2xI _{ΔN} ... 2.2xI _{ΔN} (A), I _{ΔN} <30 mA) | 0.05xI _{ΔN} | ±0.1xI _{ΔN} |
| IMPEDANCE | Zline L-L, L-N Ipsc | 0.00 Ω ... 9.99 Ω 10.0 Ω ... 99.9 Ω 100 Ω ... 999 Ω 1.00 kΩ ... 9.99 kΩ | 0.01 Ω 0.1 Ω 1 Ω 10 Ω | ±(5 % of r. + 5 digits) ±(10 % of r.) |
| | Zloop L-PE, IpfC | 0.00 Ω ... 9.99 Ω 10.0 Ω ... 99.9 Ω 100 Ω ... 999 Ω 1.00 kΩ ... 9.99 kΩ | 0.01 Ω 0.1 Ω 1 Ω 10 Ω | ±(5 % of r. + 5 digits) ±(10 % of r.) |
| VOLTAGE | TRMS | 0 ... 550 V | 1 V | ±(2 % of r. + 2 digits) |
| | Frequency | 0.00 Hz .. 9.99 Hz 10.0 Hz ... 499.9 Hz | 0.01 Hz 0.1 Hz | ±(0.2 % of r. + 1 digits) |
| EARTH RESISTANCE | 3 wire | 0.00 Ω ... 19.99 Ω 20.0 Ω ... 199.9 Ω 200.0 Ω ... 9999 Ω | 0.01 Ω 0.1 Ω 1 Ω | ±(5 % of r. + 5 digits) |
| GENERAL | Power supply | 9 VDC (6x1.5 V battery or accu, size AA) | | |
| | Overvoltage category | 1000 V DC CAT II; 600 V CAT III; 300 V CAT IV | | |
| | Protection class | double insulation | | |
| | COM port | USB, RS232 | | |
| | Weight | 1.3 kg | | |
| | Size (l x h x w) | 230 x 103 x 115 mm | | |



Uw distributeur

Hitma B.V.

Vragen over handmeters:
www.hitma-handmeters.nl

Ordering information

Standard set

MI 3100 SE



- Instrument EurotestEASI
- Schuko-plug test cable, 1.5 m
- Test lead, 3 x 1.5 m
- Test probe, 3 pcs (blue, black, green)
- Crocodile clip, 3 pcs (blue, black, green)
- Power supply adapter + 6 NiMH rechargeable batteries, size AA
- RS232 - PS/2 cable
- USB cable
- Soft carrying neck belt
- Soft carrying bag
- PC Software EuroLink PRO
- Short instruction manual
- Instruction manual on CD
- Handbook on CD
- Calibration certificate

Optional accessories

| Photo | Order No. | Description |
|-------|-----------|--|
| | A 1401 | Tip commander (3-wire) |
| | A 1314 | Plug commander |
| | A 1110 | Three phase adapter |
| | A 1111 | Three phase adapter with switch |
| | A 1201 | Insulated rod for CONTINUITY measurement |
| | A 1202 | Additional extension part for A 1201 |
| | A 1164 | Test lead, black, 50 m |
| | A 1153 | Test lead, black, 20 m |
| | A 1154 | Test lead, black, 4 m |
| | A 1292 | Upgrade code EuroLink PRO to EuroLink PRO Plus |
| | A 1431 | EuroLink Android APP |
| | A 1436 | BT dongle |
| | A 1160 | Fast charger for 8 AA batteries with a set of 6 NiMH bat., type AA |
| | S 2026 | Earth test set, 3-wire, 20 m |
| | S 2027 | Earth test set, 3-wire, 50 m |

Note! Photographs in this catalogue may slightly differ from the instruments at the time of delivery. Subject to technical change without notice.